



Eur päisch s Patentamt
European Pat nt Offic
Offic europé n des brev ts



(11) Publication number: **0 599 474 A2**

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: **93308173.9**

(51) Int. Cl.⁵: **E21B 43/26, E21B 37/06**

(22) Date of filing: **13.10.93**

(30) Priority: **19.11.92 US 949659**

(43) Date of publication of application:
01.06.94 Bulletin 94/22

(84) Designated Contracting States:
DE ES GB NL

(71) Applicant: **HALLIBURTON COMPANY**
P.O. Drawer 1431
Duncan Oklahoma 73536(US)

(72) Inventor: **Brezinski, Michael**
808 West Beech
Duncan, Oklahoma 73533(US)
Inventor: **Gardner, Tommy R.**
2809 West Beech

Duncan, Oklahoma 73533(US)

Inventor: **Harms, Weldon M.**

Route 2, Box 76

Duncan, Oklahoma 73533(US)

Inventor: **Lane, Jr., James L.**

511 North 11th Street

Duncan, Oklahoma 73533(US)

Inventor: **King, Karen L.**


Route 1, Box 16D

Duncan, Oklahoma 73533(US)

(74) Representative: **Wain, Christopher Paul et al**
A.A. THORNTON & CO.
Northumberland House
303-306 High Holborn
London WC1V 7LE (GB)

(54) **Controlling iron in aqueous well fracturing fluids.**

(57) Ferric iron contained in a fracturing fluid is prevented from precipitating or otherwise disadvantageously reacting by adding a thioalkyl acid compound to the fracturing fluid. The thioalkyl acid compound reduces ferric iron to ferrous ion which remains in solution at pH levels below about 7.5. The thioalkyl acid compound has the formula:



where n is an integer from 1 to 10; Z is R or M; R is hydrogen, $-(\text{CH}_2)_x\text{CH}_3$, $-\text{CH}_2\text{COOH}$ or $-(\text{CH}_2)_xC_6H_5$ wherein x is 0 or an integer from 1 to 6; M is sodium, potassium, ammonium, calcium, magnesium or $\text{H}_3\text{N}^+\text{OH}$; and d is 1 when Z is R, or d is 1 or 2 when Z is M to match the valence of M.

EP 0 599 474 A2

This invention broadly relates to fracturing subterranean well formations to stimulate the production of oil and/or gas therefrom and, more particularly, to controlling iron in aqueous well fracturing fluids to prevent the formation of iron precipitates therein as well as to prevent other undesirable iron reactions.

The stimulation of oil and/or gas production from subterranean formations by fracturing the formations is well known to those skilled in the art. Generally, a fracturing procedure is carried out by pumping a fracturing fluid into the formation at a rate and pressure such that the formation is hydraulically fractured. The fractures are extended in the formation by continued introduction of fracturing fluid therein, and the fractures so formed are often propped open by propping agent, e.g. sand, deposited therein. Also, depending upon the type of rock making up the formation, the fracture faces can be etched with acid to form flow channels therein. Once the fractures have been formed, propping agent has been deposited therein and/or flow channels have been formed in the faces of the fractures, the hydraulic pressure exerted on the formation is released which causes the fracturing fluid to reverse flow out of the formation and the fractures to close leaving permeable passages therein through which oil and/or gas flows from the formation to the wellbore.


A problem which can be encountered if the fracturing fluid contains dissolved iron is the precipitation of iron compounds such as ferric hydroxide therefrom. Such precipitates can plug or reduce the permeability of the fractured formation whereby the fracturing procedure results in a reduction of oil and/or gas production instead of an increase of such production.

Another problem which can be caused by the presence of dissolved iron in a fracturing fluid comprised of a gelled aqueous polymer solution is the undesirable ferric ion cross-linking of the hydrated polymer whereby the viscosity of the fracturing fluid is undesirably increased and/or inconsistent.

While iron precipitate control additives have been developed and used heretofore, the presence of such additives in viscosified aqueous fracturing fluids can significantly hasten the destruction of the viscosifying hydrated polymer in the fluids and prevent or impede the successful completion of a fracturing procedure.

We have now devised an improved method of controlling iron in an aqueous fracturing fluid whereby ferric ion therein is reduced to ferrous ion which remains in the fracturing fluid without precipitates being produced therefrom.

According to the present invention, there is provided a method of controlling iron in an aqueous fracturing fluid having a pH below 7.5, which method comprises adding a ferric ion reducing agent to said fracturing fluid in an amount sufficient to reduce ferric ion contained therein to ferrous ion, said ferric ion reducing agent being a compound of the general formula:



wherein n is an integer from 1 to 10; Z is R or M; R is hydrogen, $-(\text{CH}_2)_x\text{CH}_3$, $-\text{CH}_2\text{COOH}$ or $-(\text{CH}_2)_xC_6H_5$ wherein x is 0 or an integer from 1 to 6; M is sodium, potassium, ammonium, calcium, magnesium or $\text{H}_3\text{N}^+\text{OH}$; and d is 1 when Z is R, or d is 1 or 2 when Z is M to match the valence of M.

By the method of the invention, iron contained in an aqueous fracturing fluid having a pH below about 7.5 is controlled by adding a ferric ion reducing agent to the fracturing fluid in an amount sufficient to prevent the precipitation of ferric compounds or the undesirable cross-linking of polymer in the fracturing fluid. Also, the ferric ion reducing agents of this invention generally do not bring about fracturing fluid viscosity loss to as great a degree as prior art iron control agents used heretofore. The term "controlling" and similar terms when used herein in relation to iron contained in a fracturing fluid mean that ferric iron is reduced to ferrous iron and the pH of the fracturing fluid is maintained below about 7.5 whereby ferrous iron precipitates are not formed.

Ferric iron can find its way into aqueous fracturing fluids in various ways, the most common of which are by way of the water used in forming the fracturing fluid or by the reaction of the formed fracturing fluid with iron containing compounds in the formation being fractured. When ferric iron (+3 oxidation state) exists in the fracturing fluid, it starts to form ferric hydroxide precipitate when the pH of the fluid increases to about 2.5, and it is completely precipitated when the pH reaches about 3.5. Ferrous iron (+2 oxidation state) on the other hand, remains in solution to a pH up to about 7.5.

The fracturing fluid compositions of this invention are basically comprised of an aqueous solution, e.g. a gelled aqueous polymer solution or a cross-linked gelled aqueous polymer solution, and the ferric ion reducing agent. The compositions may also include one or more buffering agents to help maintain the pH of the fracturing fluid below about 7.5, preferably in the pH range of from about 1 to about 5. In addition, the compositions can include one or more other agents often added to well treatment fluids including additives for removing oxygen therefrom. Also, when the formation being fractured contains reactive sulfides, the fracturing fluid can include one or more agents for preventing the precipitation of ferrous sulfide.

A preferred ferric iron reducing agent is a compound of the above formula wherein n is 1, d is 1 and Z is R. The most preferred ferric iron reducing agent is thioglycolic acid. Other reducing agent which may be used include, for example, α -methylthioglycolic acid, methylthioglycolate, α,α -dimethylthioglycolic acid, α -phenylthioglycolic acid, methyl- α -methylthioglycolate, benzylthioglycolate, α -benzylthioglycolic acid, ammonium thioglycolate, hydroxylammonium thioglycolate, calcium dithioglycolate, β -thiopropionic acid, methyl- β -thiopropionate, sodium- β -thiopropionate and thiomalic acid.

The amount of ferric ion reducing agent effective to reduce substantially all of the ferric ion contained in, or to be contained in, a fracturing fluid composition of this invention depends on the temperature of the reduction reaction environment. A satisfactory rate of reduction is provided by an amount of ferric ion reducing agent which will produce the required reduction in about 1 hour. Generally, the ferric ion reducing agent is combined with a fracturing fluid in a minimum amount of about 0.01% by volume of the fracturing fluid to a maximum amount of about 8% by volume of the fracturing fluid.

A variety of aqueous solutions can be utilized for forming the fracturing fluid compositions of this invention. Generally, the aqueous solution is comprised of water having one or more viscosity increasing hydratable polymers dissolved therein. Examples of commonly utilized such polymers are polysaccharides including galactomannan polymers, glucomannan polymers and their derivatives. Typical of such polymers are guar gum and guar derivatives and modified cellulose such as hydroxyethylcellulose, carboxymethylcellulose, xanthan gum and other cellulose derivatives. Synthetic polymers can also be utilized examples of which include polyacrylamides, poly-2-amino-2-methyl propane sulfonic acid and others. The polymer is generally present in the aqueous solution in an amount in the range of from about 0.1% to about 2% by weight of solution to thereby produce a gelled aqueous polymer fluid having an apparent viscosity in the range of from about 2 cp to about 200 cp as determined using a Fann Model 50 viscometer. The particular concentration of the polymer depends upon the conditions of the well to be fractured and other factors well known to those skilled in the art.

As mentioned above, aqueous polymer solutions can be cross-linked to increase their viscosity by adding a cross-linking compound thereto. Typical such cross-linking compounds are organic chelates of titanium, zirconium, aluminum or other multivalent metals. The selection of an appropriate cross-linking compound depends upon the particular polymer used, and the amount of cross-linking compound depends upon the well conditions and other factors. Generally, a cross-linking compound is added to an aqueous polymer solution in an amount in the range of from about 0.0005% to about 1.2% by weight of the solution to produce a cross-linked gelled aqueous polymer fluid having a viscosity in the range of from about 40 cp to about 6000 cp (0.04 to 6 Pa s) as determined using a Fann Model 50 viscometer.

As mentioned above, the gelled aqueous polymer fracturing fluid and/or gelled aqueous cross-linked polymer fracturing fluid must have a pH below about 7.5 to prevent the precipitation of ferrous compounds therefrom. The pH of the fracturing fluid composition can be adjusted if necessary using acids, buffering agents and mixtures of acids and bases. Preferably, the pH of the fracturing fluid is adjusted to a level in the range of from about 1 to about 5 and a buffering agent selected from the group consisting of carbon dioxide, organic acids, e.g., acetic or formic acid, acid salts, e.g., ammonium bisulfite and inorganic acids, e.g., hydrochloric acid or sulfuric acid is added to the fracturing fluid to maintain the pH within that range. The most preferred buffering agent is formic acid.

Other components and additives that can be combined with the compositions of the present invention include acids, sulfide reactants or scavengers such as aldehydes or ketones, surfactants, corrosion inhibitors, fluid loss additives, biocides, non-emulsifying agents and mutual solvents. Such components and additives are well known to those skilled in the art, and their use depends on the conditions of the subterranean formation to be fractured and other factors.

In order to further illustrate the methods and compositions of the present invention, the following examples are given.

Exempl 1

A quantity of an aqueous treatment fluid recovered from the Antrim Shale formation containing ferric hydroxide precipitate (90 ppm ferric ion) was obtained having a pH of 6.26. The aqueous suspension of ferric hydroxide was divided into samples and various iron control additives including a ferric ion reducing agent of this invention were added to the samples in quantities equivalent to 20 pounds (9.06kg) of additive per 1000 U.S. gallons (3.79m³) of aqueous suspension. The ferric ion reducing agent of the present invention used was thioglycolic acid and the other additives were prior art iron control additives, namely, citric acid, hydroxylamine and the ferric ion reducing composition described in United States Patent No. 4,683,954 issued on August 4, 1987, i.e., a mixture of hydroxylamine hydrochloride, gluconodeltalactone and a catalytic amount of cuprous ion.

The samples containing the additives were heated from ambient to 125 °F (51 °C) over a time period of about 1 hour. None of the prior art additives reacted with the aqueous ferric hydroxide suspension which retained its original opaque orange color. The sample to which the thioglycolic acid was added reacted whereby the ferric ion in the precipitate was reduced to ferrous ion and dissolved. As the reaction took place, the suspension was converted from opaque orange to a clear colorous solution.

Example 2

An aqueous fracturing fluid containing a guar gum viscosifying polymer in an amount of about 0.36% by weight of the aqueous polymer solution was prepared having a viscosity of 19.5 cp(.0195 Pa s) as determined by a Fann Model 50 viscometer. The polymer solution was divided into two test samples, to one of which was added thioglycolic acid in an amount of 0.05% by weight of the resulting solution. The ferric ion reducing composition described in U.S. Patent No. 4,683,954 issued on August 4, 1987, i.e., a mixture of hydroxylamine hydrochloride, gluconodeltalactone and a catalytic amount of cuprous ion was added to the other polymer solution sample in an amount of about 0.12% by weight of the resulting solution. The viscosities of the test samples containing the additives were continuously monitored over time after the addition of the additives utilizing a Fann Model 50 viscometer at 300 rpm. The results of the tests are set forth and compared in the Table below.

TABLEAdditive Effect on Fracturing Fluid Viscosity

Additive	Additive Quantity, % by wt.	Initial	Viscosity, cp (Pa s)							
			4 min.	5 min.	7 min.	9 min.	15 min.	20 min.	25 min.	30 min.
Additive of this Invention ¹	0.36	19.5 (.0195)	19.5 (.0195)	19.0 (.019)	19.0 (.019)	19.0 (.019)	18.5 (.0185)	18.5 (.0185)	18.0 (.018)	18.0 (.018)
Prior Art Additive ²	0.36	19.5 (.0195)	19.0 (.019)	18.5 (.0185)	18.0 (.018)	17.5 (.0175)	15.5 (.0155)	14.0 (.014)	12.0 (.012)	11.0 (.011)

¹ Thioglycolic acid


² hydroxylamine hydrochloride-gluconodeltalactone-cuprous ion additive of U.S. Patent No. 4,683,954

From Table I it can be seen that the ferric ion reducing additive of the present invention causes viscosity reduction to a substantially lesser degree than does the prior art additive tested.

Claims

1. A method of controlling iron in an aqueous fracturing fluid having a pH below 7.5, which method comprises adding a ferric ion reducing agent to said fracturing fluid in an amount sufficient to reduce ferric ion contained therein to ferrous ion, said ferric ion reducing agent being a compound of the

general formula:



wherein n is an integer from 1 to 10; Z is R or M; R is hydrogen, $-(\text{CH}_2)_x\text{CH}_3$, $-\text{CH}_2\text{COOH}$ or $-(\text{CH}_2)_x\text{C}_6\text{H}_5$ wherein x is 0 or an integer from 1 to 6; M is sodium, potassium, ammonium, calcium, magnesium or $\text{H}_3\text{N}^+\text{OH}$; and d is 1 when Z is R, or d is 1 or 2 when Z is M to match the valence of M.

- 15
2. A method according to claim 1, wherein the reducing agent is added to the aqueous fracturing fluid in an amount of from 0.01% to 8% by volume of said fracturing fluid.
3. A method according to claim 1 or 2, wherein n is 1, d is 1 and Z is R.
- 20
4. A method according to claim 1, 2 or 3, wherein the reducing agent is thioglycolic acid.
5. A method according to claim 1, 2, 3 or 4, wherein the aqueous fracturing fluid is a gelled aqueous polymer solution, a cross-linked gelled aqueous polymer solution, or an emulsion or foam containing a gelled aqueous polymer solution or cross-linked gelled aqueous polymer solution.
- 25
6. A method according to claim 5, wherein the fracturing fluid is a gelled aqueous polymer solution containing polymer in an amount of from 0.1% to 2% by weight of said solution.
- 30
7. A method according to any of claims 1 to 6, which further comprises adding a buffering agent to the fracturing fluid to maintain the pH of said fracturing fluid in the range from 1 to 5.
8. A method according to claim 7, wherein the buffering agent is carbon dioxide, an organic acid, an acid salt or an inorganic acid.
- 35
9. A method according to claim 8, wherein the buffering agent is formic acid.
10. A method of fracturing a subterranean well formation wherein there is used a fracturing fluid made by the method of any of claims 1 to 9.
- 40

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets




(11) Publication number:

0 599 474 A3

(12)

EUROPEAN PATENT APPLICATION(21) Application number: **93308173.9**(51) Int. Cl.⁵: **E21B 43/26, E21B 37/06,
C02F 5/08**(22) Date of filing: **13.10.93**(30) Priority: **19.11.92 US 949659**(43) Date of publication of application:
01.06.94 Bulletin 94/22(84) Designated Contracting States:
DE ES GB NL(88) Date of deferred publication of the search report:
02.11.94 Bulletin 94/44(71) Applicant: **HALLIBURTON COMPANY**
P.O. Drawer 1431
Duncan Oklahoma 73536 (US)(72) Inventor: **Brezinski, Michael**
808 West Beech
Duncan, Oklahoma 73533 (US)
Inventor: **Gardner, Tommy R.**
2809 West Beech
Duncan, Oklahoma 73533 (US)
Inventor: **Harms, Weldon M.**
Route 2, Box 76
Duncan, Oklahoma 73533 (US)
Inventor: **Lane, Jr., James L.**
511 North 11th Street
Duncan, Oklahoma 73533 (US)
Inventor: **King, Karen L.**
Route 1, Box 16D
Duncan, Oklahoma 73533 (US)(74) Representative: **Wain, Christopher Paul et al**
A.A. THORNTON & CO.
Northumberland House
303-306 High Holborn
London WC1V 7LE (GB)(54) **Controlling Iron in aqueous well fracturing fluids.**

(57) Ferric iron contained in a fracturing fluid is prevented from precipitating or otherwise disadvantageously reacting by adding a thioalkyl acid compound to the fracturing fluid. The thioalkyl acid compound reduces ferric ion to ferrous ion which remains in solution at pH levels below about 7.5. The thioalkyl acid compound has the formula:



where n is an integer from 1 to 10; Z is R or M; R is hydrogen, $-(\text{CH}_2)_x\text{CH}_3$, $-\text{CH}_2\text{COOH}$ or $-(\text{CH}_2)_x\text{C}_6\text{H}_5$ wherein x is 0 or an integer from 1 to 6; M is sodium, potassium, ammonium, calcium, magnesium

EP 0 599 474 A3

EP 0 599 474 A3

or $\text{H}_3\text{N}^+\text{OH}$; and d is 1 when Z is R, or d is 1 or 2 when Z is M to match the valence of M.



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 93 30 8173

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.5)
A	DATABASE WPI Week 8341, 5 September 1983 Derwent Publications Ltd., London, GB; AN 786537 & JP-A-58 148 964 (JIYUN OKUDA) * abstract * -----	1	E21B43/26 E21B37/06 C02F5/08
			TECHNICAL FIELDS SEARCHED (Int.Cl.5)
			E21B C02F
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 9 September 1994	Examiner Van Belleghem, W
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons Δ : member of the same patent family, corresponding document			

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 599 474 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
17.12.1997 Bulletin 1997/51

(51) Int Cl.⁶: **E21B 43/26, E21B 37/06,
C02F 5/08**

(21) Application number: **93308173.9**

(22) Date of filing: **13.10.1993**

(54) Controlling iron in aqueous well fracturing fluids

Kontrollieren von Eisenniederschlägen in wässrigen Bohrlochfrakturierungsflüssigkeiten

Contrôler l'encroisement par le fer dans des fluides aqueuses pour la fracturation de puits de pétrole

(84) Designated Contracting States:
DE ES GB NL

(30) Priority: **19.11.1992 US 949659**

(43) Date of publication of application:
01.06.1994 Bulletin 1994/22

(73) Proprietor: **Halliburton Energy Services, Inc.
Duncan, Oklahoma 73536 (US)**

(72) Inventors:
• **Brezinski, Michael
Duncan, Oklahoma 73533 (US)**
• **Gardner, Tommy R.
Duncan, Oklahoma 73533 (US)**

- **Harms, Weldon M.
Duncan, Oklahoma 73533 (US)**
- **Lane, Jr., James L.
Duncan, Oklahoma 73533 (US)**
- **King, Karen L.
Duncan, Oklahoma 73533 (US)**

(74) Representative: **Wain, Christopher Paul et al
A.A. THORNTON & CO.
Northumberland House
303-306 High Holborn
London WC1V 7LE (GB)**

(56) References cited:
• **DATABASE WPI Week 8341, 5 September 1983
Derwent Publications Ltd., London, GB; AN
786537 & JP-A-58 148 964 (JIYUN OKUDA)**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 599 474 B1

Description

This invention broadly relates to fracturing subterranean well formations to stimulate the production of oil and/or gas therefrom and, more particularly, to controlling iron in aqueous well fracturing fluids to prevent the formation of iron precipitates therein as well as to prevent other undesirable iron reactions.

The stimulation of oil and/or gas production from subterranean formations by fracturing the formations is well known to those skilled in the art. Generally, a fracturing procedure is carried out by pumping a fracturing fluid into the formation at a rate and pressure such that the formation is hydraulically fractured. The fractures are extended in the formation by continued introduction of fracturing fluid therein, and the fractures so formed are often propped open by propping agent, e.g. sand, deposited therein. Also, depending upon the type of rock making up the formation, the fracture faces can be etched with acid to form flow channels therein. Once the fractures have been formed, propping agent has been deposited therein and/or flow channels have been formed in the faces of the fractures, the hydraulic pressure exerted on the formation is released which causes the fracturing fluid to reverse flow out of the formation and the fractures to close leaving permeable passages therein through which oil and/or gas flows from the formation to the wellbore.


A problem which can be encountered if the fracturing fluid contains dissolved iron is the precipitation of iron compounds such as ferric hydroxide therefrom. Such precipitates can plug or reduce the permeability of the fractured formation whereby the fracturing procedure results in a reduction of oil and/or gas production instead of an increase of such production.

Another problem which can be caused by the presence of dissolved iron in a fracturing fluid comprised of a gelled aqueous polymer solution is the undesirable ferric ion cross-linking of the hydrated polymer whereby the viscosity of the fracturing fluid is undesirably increased and/or inconsistent.

While iron precipitate control additives have been developed and used heretofore, the presence of such additives in viscosified aqueous fracturing fluids can significantly hasten the destruction of the viscosifying hydrated polymer in the fluids and prevent or impede the successful completion of a fracturing procedure.

We have now devised an improved method of controlling iron in an aqueous fracturing fluid whereby ferric ion therein is reduced to ferrous ion which remains in the fracturing fluid without precipitates being produced therefrom.

According to the present invention, there is provided a method of controlling iron in an aqueous fracturing fluid having a pH below 7.5, which method comprises adding a ferric ion reducing agent to said fracturing fluid in an amount sufficient to reduce ferric ion contained therein to ferrous ion, said ferric ion reducing agent being a compound of the general formula:



wherein n is an integer from 1 to 10; Z is R or M; R is hydrogen, $-(\text{CH}_2)_x\text{CH}_3$, $-\text{CH}_2\text{COOH}$ or $-(\text{CH}_2)_x\text{C}_6\text{H}_5$ wherein x is 0 or an integer from 1 to 6; M is sodium, potassium, ammonium, calcium, magnesium or $\text{H}_3\text{N}^+\text{OH}$; and d is 1 when Z is R, or d is 1 or 2 when Z is M to match the valence of M.

By the method of the invention, iron contained in an aqueous fracturing fluid having a pH below about 7.5 is controlled by adding a ferric ion reducing agent to the fracturing fluid in an amount sufficient to prevent the precipitation of ferric compounds or the undesirable cross-linking of polymer in the fracturing fluid. Also, the ferric ion reducing agents of this invention generally do not bring about fracturing fluid viscosity loss to as great a degree as prior art iron control agents used heretofore. The term "controlling" and similar terms when used herein in relation to iron contained in a fracturing fluid mean that ferric iron is reduced to ferrous iron and the pH of the fracturing fluid is maintained below about 7.5 whereby ferrous iron precipitates are not formed.

Ferric iron can find its way into aqueous fracturing fluids in various ways, the most common of which are by way of the water used in forming the fracturing fluid or by the reaction of the formed fracturing fluid with iron containing compounds in the formation being fractured. When ferric iron (+3 oxidation state) exists in the fracturing fluid, it starts to form ferric hydroxide precipitate when the pH of the fluid increases to about 2.5, and it is completely precipitated when the pH reaches about 3.5. Ferrous iron (+2 oxidation state) on the other hand, remains in solution to a pH up to about 7.5.

The fracturing fluid compositions of this invention are basically comprised of an aqueous solution, e.g. a gelled aqueous polymer solution or a cross-linked gelled aqueous polymer solution, and the ferric ion reducing agent. The

compositions may also include one or more buffering agents to help maintain the pH of the fracturing fluid below about 7.5, preferably in the pH range of from about 1 to about 5. In addition, the compositions can include one or more other agents often added to well treatment fluids including additives for removing oxygen therefrom. Also, when the formation being fractured contains reactive sulfides, the fracturing fluid can include one or more agents for preventing the precipitation of ferrous sulfide.

A preferred ferric iron reducing agent is a compound of the above formula wherein n is 1, d is 1 and Z is R. The most preferred ferric iron reducing agent is thioglycolic acid. Other reducing agent which may be used include, for example, α -methylthioglycolic acid, methylthioglycolate, α,α -dimethylthioglycolic acid, α -phenylthioglycolic acid, methyl- α -methylthioglycolate, benzylthioglycolate, α -benzylthioglycolic acid, ammonium thioglycolate, hydroxylammonium thioglycolate, calcium dithioglycolate, β -thiopropionic acid, methyl- β -thiopropionate, sodium- β -thiopropionate and thiomalic acid.

The amount of ferric ion reducing agent effective to reduce substantially all of the ferric ion contained in, or to be contained in, a fracturing fluid composition of this invention depends on the temperature of the reduction reaction environment. A satisfactory rate of reduction is provided by an amount of ferric ion reducing agent which will produce the required reduction in about 1 hour. Generally, the ferric ion reducing agent is combined with a fracturing fluid in a minimum amount of about 0.01% by volume of the fracturing fluid to a maximum amount of about 8% by volume of the fracturing fluid.

A variety of aqueous solutions can be utilized for forming the fracturing fluid compositions of this invention. Generally, the aqueous solution is comprised of water having one or more viscosity increasing hydratable polymers dissolved therein. Examples of commonly utilized such polymers are polysaccharides including galactomannan polymers, glucomannan polymers and their derivatives. Typical of such polymers are guar gum and guar derivatives and modified cellulose such as hydroxyethylcellulose, carboxymethylcellulose, xanthan gum and other cellulose derivatives. Synthetic polymers can also be utilized examples of which include polyacrylamides, poly-2-amino-2-methyl propane sulfonic acid and others. The polymer is generally present in the aqueous solution in an amount in the range of from about 0.1% to about 2% by weight of solution to thereby produce a gelled aqueous polymer fluid having an apparent viscosity in the range of from about 2 cp to about 200 cp as determined using a Fann Model 50 viscometer. The particular concentration of the polymer depends upon the conditions of the well to be fractured and other factors well known to those skilled in the art.

As mentioned above, aqueous polymer solutions can be cross-linked to increase their viscosity by adding a cross-linking compound thereto. Typical such cross-linking compounds are organic chelates of titanium, zirconium, aluminum or other multivalent metals. The selection of an appropriate cross-linking compound depends upon the particular polymer used, and the amount of cross-linking compound depends upon the well conditions and other factors. Generally, a cross-linking compound is added to an aqueous polymer solution in an amount in the range of from about 0.0005% to about 1.2% by weight of the solution to produce a cross-linked gelled aqueous polymer fluid having a viscosity in the range of from about 40 cp to about 6000 cp (0.4 to 6 Pa s) as determined using a Fann Model 50 viscometer.

As mentioned above, the gelled aqueous polymer fracturing fluid and/or gelled aqueous cross-linked polymer fracturing fluid must have a pH below about 7.5 to prevent the precipitation of ferrous compounds therefrom. The pH of the fracturing fluid composition can be adjusted if necessary using acids, buffering agents and mixtures of acids and bases. Preferably, the pH of the fracturing fluid is adjusted to a level in the range of from about 1 to about 5 and a buffering agent selected from the group consisting of carbon dioxide, organic acids, e.g., acetic or formic acid, acid salts, e.g., ammonium bisulfite and inorganic acids, e.g., hydrochloric acid or sulfuric acid is added to the fracturing fluid to maintain the pH within that range. The most preferred buffering agent is formic acid.

Other components and additives that can be combined with the compositions of the present invention include acids, sulfide reactants or scavengers such as aldehydes or ketones, surfactants, corrosion inhibitors, fluid loss additives, biocides, non-emulsifying agents and mutual solvents. Such components and additives are well known to those skilled in the art, and their use depends on the conditions of the subterranean formation to be fractured and other factors.

In order to further illustrate the methods and compositions of the present invention, the following examples are given.

Example 1

A quantity of an aqueous treatment fluid recovered from the Antrim Shale formation containing ferric hydroxide precipitate (90 ppm ferric ion) was obtained having a pH of 6.26. The aqueous suspension of ferric hydroxide was divided into samples and various iron control additives including a ferric ion reducing agent of this invention were added to the samples in quantities equivalent to 20 pounds (9.06kg) of additive per 1000 U.S. gallons (3.79m³) of aqueous suspension. The ferric ion reducing agent of the present invention used was thioglycolic acid and the other additives were prior art iron control additives, namely, citric acid, hydroxylamine and the ferric ion reducing composition described in United States Patent No. 4,683,954 issued on August 4, 1987, i.e., a mixture of hydroxylamine hydrochloride, glu-

conodeltalactone and a catalytic amount of cuprous ion.

The samples containing the additives were heated from ambient to 125°F (51°C) over a time period of about 1 hour. None of the prior art additives reacted with the aqueous ferric hydroxide suspension which retained its original opaque orange color. The sample to which the thioglycolic acid was added reacted whereby the ferric ion in the precipitate was reduced to ferrous ion and dissolved. As the reaction took place, the suspension was converted from opaque orange to a clear colorous solution.

Example 2

An aqueous fracturing fluid containing a guar gum viscosifying polymer in an amount of about 0.36% by weight of the aqueous polymer solution was prepared having a viscosity of 19.5 cp(.0195 Pa s) as determined by a Fann Model 50 viscometer. The polymer solution was divided into two test samples, to one of which was added thioglycolic acid in an amount of 0.05% by weight of the resulting solution. The ferric ion reducing composition described in U.S. Patent No. 4,683,954 issued on August 4, 1987, i.e., a mixture of hydroxylamine hydrochloride, gluconodeltalactone and a catalytic amount of cuprous ion was added to the other polymer solution sample in an amount of about 0.12% by weight of the resulting solution. The viscosities of the test samples containing the additives were continuously monitored over time after the addition of the additives utilizing a Fann Model 50 viscometer at 300 rpm. The results of the tests are set forth and compared in the Table below.

TABLE

Additive Effect on Fracturing Fluid Viscosity										
Additive	Additive Quantity, % by wt.	Initial	Viscosity, cp (Pa s)							
			4 min.	5 min.	7 min.	9 min.	15 min.	20 min.	25 min.	30 min.
Additive of this Invention ¹	0.36	19.5 (.0195)	19.5 (.0195)	19.0 (.019)	19.0 (.019)	19.0 (.019)	18.5 (.0185)	18.5 (.0185)	18.0 (.018)	18.0 (.018)
Prior Art Additive ²	0.36	19.5 (.0195)	19.0 (.019)	18.5 (.0185)	18.0 (.018)	17.5 (.0175)	15.5 (.0155)	14.0 (.014)	12.0 (.012)	11.0 (.011)


¹ Thioglycolic acid

² hydroxylamine hydrochloride-gluconodeltalactone-cuprous ion additive of U.S. Patent No. 4,683,954

From Table I it can be seen that the ferric ion reducing additive of the present invention causes viscosity reduction to a substantially lesser degree than does the prior art additive tested.

Claims

1. A method of controlling iron in an aqueous fracturing fluid having a pH below 7.5, which method comprises adding a ferric ion reducing agent to said fracturing fluid in an amount sufficient to reduce ferric ion contained therein to ferrous ion, said ferric ion reducing agent being a compound of the general formula:




wherein n is an integer from 1 to 10; Z is R or M; R is hydrogen, $-(\text{CH}_2)_x\text{CH}_3$, $-\text{CH}_2\text{COOH}$ or $-(\text{CH}_2)_xC_6\text{H}_5$ wherein x is 0 or an integer from 1 to 6; M is sodium, potassium, ammonium, calcium, magnesium or $\text{H}_3\text{N}^+\text{OH}$; and d is 1 when Z is R, or d is 1 or 2 when Z is M to match the valence of M.

2. A method according to claim 1, wherein the reducing agent is added to the aqueous fracturing fluid in an amount of from 0.01% to 8% by volume of said fracturing fluid.
3. A method according to claim 1 or 2, wherein n is 1, d is 1 and Z is R.
4. A method according to claim 1, 2 or 3, wherein the reducing agent is thioglycolic acid.
5. A method according to claim 1, 2, 3 or 4, wherein the aqueous fracturing fluid is a gelled aqueous polymer solution, a cross-linked gelled aqueous polymer solution, or an emulsion or foam containing a gelled aqueous polymer solution or cross-linked gelled aqueous polymer solution.
6. A method according to claim 5, wherein the fracturing fluid is a gelled aqueous polymer solution containing polymer in an amount of from 0.1% to 2% by weight of said solution.
7. A method according to any of claims 1 to 6, which further comprises adding a buffering agent to the fracturing fluid to maintain the pH of said fracturing fluid in the range from 1 to 5.
8. A method according to claim 7, wherein the buffering agent is carbon dioxide, an organic acid, an acid salt or an inorganic acid.
9. A method according to claim 8, wherein the buffering agent is formic acid.
10. A method of fracturing a subterranean well formation wherein there is used a fracturing fluid made by the method of any of claims 1 to 9.

Patentansprüche

1. Eine Vorgehensweise der Kontrolle von Eisen in einer wässrigen Spaltflüssigkeit mit einem pH-Wert unter 7,5, bestehend aus dem Beimischen eines Eisen(III)-ionen-Reduktionsmittels zur o.g. Spaltflüssigkeit in einer Menge, die ausreicht, um die dann befindlichen Eisen(III)-ionen auf Eisen(II)-ionen zu reduzieren. Das o.g. Eisen(III)-ionen-Reduktionsmittel ist dabei eine Mischung mit der folgenden allgemeinen Formel:




wobei n eine Ganzzahl von 1 bis 10 ist; Z ist R oder M; R ist Wasserstoff, $-(\text{CH}_2)_x \text{CH}_3$, $-\text{CH}_2\text{COOH}$ oder $-(\text{CH}_2)_x \text{C}_6\text{H}_5$, wobei x 0 oder eine Ganzzahl von 1 bis 6 ist; M ist Natrium, Potassium, Ammonium, Calcium, Magnesium oder $\text{H}_3\text{N}^+\text{OH}$ und d ist 1, wenn Z = R ist oder d ist 1 oder 2, wenn Z = M ist, um der Valenz von M zu entsprechen.

2. Eine Vorgehensweise nach Anspruch 1, bei der das Reduktionsmittel der wässrigen Spaltflüssigkeit in einer Menge zwischen 0,01% bis 8% Vol. der o.g. Spaltflüssigkeit beigemischt wird.
3. Eine Vorgehensweise nach Anspruch 1 oder 2, bei der n = 1, d = 1 und Z = R ist.
4. Eine Vorgehensweise nach einem der Ansprüche 1, 2 oder 3, bei der das Reduktionsmittel Thioglykolsäure ist.
5. Eine Vorgehensweise nach einem der Ansprüche 1, 2, 3 oder 4, bei der die wässrige Spaltflüssigkeit eine gelierte wässrige Polymerlösung, eine vernetzte, gelierte, wässrige Polymerlösung, eine Emulsion oder einen Schaum darstellt, der eine gelierte, wässrige Polymerlösung oder eine vernetzte, gelierte, wässrige Polymerlösung enthält.

6. Eine Vorgehensweise nach Anspruch 5, bei der die Spaltflüssigkeit eine gelierte, wässrige Polymerlösung mit Polymergehalt von 0,1 bis 2 % Massenanteil der Lösung enthält.
7. Eine Vorgehensweise nach einem der Ansprüche 1 bis 6, die weiter aus dem Beimischen eines Puffermittels zur Spaltflüssigkeit besteht, um den pH-Wert der o.g. Spaltflüssigkeit im Bereich von 1 bis 5 zu halten.
8. Eine Vorgehensweise nach Anspruch 7, bei der das Puffermittel Kohlendioxid, eine organische Säure, ein Säuresalz oder eine anorganische Säure ist.
9. Eine Vorgehensweise nach Anspruch 8, bei der das Puffermittel Ameisensäure ist. Eine Vorgehensweise der Spaltung einer unterirdischen Bohrlochformation, bei der eine Spaltflüssigkeit benutzt wird, die nach den Vorgehensweisen eines der Ansprüche 1 bis 9 zubereitet wurde.
10. Eine Vorgehensweise der Spaltung einer unterirdischen Bohrlochformation, bei der eine Spaltflüssigkeit benutzt wird, die nach den Vorgehensweisen eines der Ansprüche 1 bis 9 zubereitet wurde.

Revendications

1. Une méthode de contrôle du fer dans un fluide de fracturation aqueux ayant un pH inférieur à 7,5, ladite méthode comportant l'ajout d'un agent réducteur d'ion ferrique audit fluide de fracturation en une quantité suffisante pour réduire l'ion ferrique qu'il contient en ion ferreux, ledit agent réducteur d'ion ferrique étant un composé possédant la formule générale :



n est un nombre entier entre 1 et 10; Z est R ou M; R est l'hydrogène, $-(\text{CH}_2)_x\text{CH}_3$, $-\text{CH}_2\text{COOH}$ ou $-(\text{CH}_2)_x\text{C}_6\text{H}_5$ dans lesquels x est 0 ou un nombre entier de 1 à 6; M est le sodium, le potassium, l'ammonium, le calcium, le magnésium ou $\text{H}_3\text{N}^+\text{OH}$; et d est 1 quand Z est R, ou d est 1 ou 2 quand Z est M pour concorder avec la valence de M.

2. Une méthode selon la revendication 1, selon laquelle l'agent réducteur est ajouté au fluide de fracturation aqueux en une quantité de 0,01% à 8% du volume du dit fluide de fracturation.
3. Une méthode selon la revendication 1 ou 2, selon laquelle n est 1, d est 1 et Z est R.
4. Une méthode selon la revendication 1, 2 ou 3, selon laquelle l'agent réducteur est l'acide thioglycolique.
5. Une méthode selon la revendication 1,2,3 ou 4, selon laquelle le fluide de fracturation aqueux est une solution d'un polymère aqueux gélifié, une solution d'un polymère aqueux gélifié réticulé, ou une émulsion ou une mousse contenant une solution d'un polymère aqueux gélifié ou une solution d'un polymère aqueux gélifié réticulé.
6. Une méthode selon la revendication 5, selon laquelle le fluide de fracturation est une solution d'un polymère aqueux gélifié contenant le polymère en une quantité de 0,1% à 2% du poids de ladite solution.
7. Une méthode selon l'une quelconque des revendications 1 à 6, qui comprend de plus l'ajout d'un agent tampon au fluide de fracturation pour maintenir le pH du dit fluide de fracturation dans la plage de 1 à 5.
8. Une méthode selon la revendication 7, selon laquelle le tampon est l'anhydride carbonique, un acide organique, un sel acide ou un acide inorganique.

EP 0 599 474 B1

9. Une méthode selon la revendication 8, selon laquelle le tampon est l'acide formique.

10. Une méthode de fracturation d'une formation de puits souterrain, utilisant un fluide de fracturation élaboré selon la méthode de l'une quelconque des revendications 1 à 9.

5

10

15

20

25

30

35

40

45

50

55